EI-D/Tech-050/6/2014-VSAT ERNET India, New Delhi

Subject: Tender for Procurement of items and services for ERNET India's VSAT Network

This is with reference to the pre-bid queries received to ERNET India in respect of Tender no. EI-D/Tech-050/6/2014-VSAT dated 19.10.2015 for Procurement of items and services for ERNET India's VSAT Network.

2. The response of ERNET India to the pre-bid queries received to us from our various prospective bidders are given at Annexure-I enclosed herewith.

3. The bidders are requested to submit their bid in confirmity with tender no. EI-D/Tech-050/6/2014-VSAT dated 19.10.2015 and subsequent ERNET India's response (on the queries received) attached herewith at Annexure-I. Other terms of tender shall remain same.

Registrar & Director (P&A) Date: 10.11.2015

ERNET India, New Delhi

Responses to the queries of prospective bidders are given below:

Ref: Tender for the Procurement of items and services for ERNET India's VSAT Network (Tender No: EI-D/Tech-050/6/2014-VSAT Date: 19.10.2015)

Note:

- 1. Tender clause statement (written in the below table) can be full or partial statement. Thus, it's starting and end point shall be read carefully. Other parts/sub-parts of the clause shall remain unchanged.
- 2. The queries of the prospective bidders which are not replied/given/addressed here are not considered by ERNET India. Thus, such clauses remain unchanged.
- 3. Responses are given below Section wise. Thus, Sections shall be seen carefully.

Sect	tion-B					
1.	Tender clause no. & Page	Clause 10.1 Page 8				
	Tender clause statement	The bidder shall confirmAnnexure-IV.				
	Queries sought (in brief)	Future variation in Govt. levies/taxes shall be born by the purchaser is not clear.				
	ERNET India's response	A new clause no. 10.5 has been added. It is given below:				
	Clause 10.5	Any variation in central/state Govt (of India) taxes, like sales tax, VAT, custom duty, octroi, etc in future and during the validity of the rate contract will be applicable and same will be born by the purchaser as per Govt rules.				
2.	Tender clause no. & Page	Clause 14.5	Page 10			
	Tender clause statement	Bids from bidders withoutis give at Annexure-VI.				
	Queries sought (in brief)	Is it essential for bidder to submit the OEMs signatory power of Attorney? (in reference to Note in Annexure-VI)				
	ERNET India's response	The submission of OEM's signatory power of attorney is not mandatory. But, the compliance shall be provided by the bidder.				
3.	Tender clause no. & Page	Clause 22.1	page 14			
	Tender clause statement	The successful bidderat any point of time.				
	Queries sought (in brief)	 ⇒ LD is very high, please amend this to 0.5% to 5% on the delayed value of goods only. ⇒ Also, suggested to add "If the bidder has commissioned 75% of the ordered sites and 100% of the hub components, LD will be applicable on the value of undelivered portion and if 75% remote sites are not commissioned in the stipulated time period then LD will be applicable on the total PO value. The intent for asking for this relaxation is that all the sites are in remote places. Even a single issue in any of the sites can result in huge penalties. ⇒ Please provide definition of unacceptable delay. 				
	ERNET India's response	Modified Tender clause statement is given below:				
	Modified Tender clause statement	"The successful bidder shall complete the awarded contract (work) on turnkey basis as per terms and conditions of the tender. If the successful Bidder fails to complete awarded work in time, bidder shall pay to ERNET India without prejudice to any other rights or remedy as may be available to ERNET India, a compensation amount calculated @ 1% of the total value of the awarded work per week subject to a maximum of 10% of POs value. In case				

		of delay in execution and completion of work, ERNET India may consider to cance awarded work order at any point of time.			
		In case commissioning of less than 10% remote VSAT sites gets delayed (due to reason the part of bidder) of the ordered value, LD will be applicable only for work pertaining these sites and not on the full awarded work/POs.			
		But, in case commissioning of these 10% removes weeks from the specified given time in the Time the part of bidder, than the bidder shall be liable	e Schedule (Annexure-III) due to reasons at e to pay penalty on the full value of POs.		
4.	Tender clause no. & Page	Clause 24.1	Page 15		
	Tender clause statement	In the event of anyincluding the ru	les framed there under.		
	Queries sought (in brief)	Request that as a sole arbitrator appointed by E parties have not mutually agreed on a neutral ar			
	ERNET India's	Modified clause is given below:			
	response	Ŭ			
	Modified Tender clause statement	In the event of any dispute or disagreement und or over the interpretation of any terms hereinab	ove contained or any claim or liability of		
		the party, the same shall be referred to the sole consent of both parties therein. The intending p other party notifying its intention for appointme	arty will serve notice in writing upon the ent of Arbitrator. Should both parties fail to		
		agree on by mutual consent, then the Arbitrator Arbitration and Conciliation Act, 1996. The pro-	ovisions of Arbitration and Conciliation		
		Act, 1996 will apply. The arbitration proceeding Arbitrator will give reasons for his award and the			
		final and binding upon the parties herein. Such			
		submission to arbitration under the Indian Arbit any modifications or reenactment there of inclu			
5.	Tender clause no. & Page	Clause 28.2	Page 16		
	Tender clause statement	Delays in the bidder's Performance			
	Queries sought (in brief)	Requested to quantify the delay as 90 days be which is 15 Weeks.	yond the stipulated completion schedule		
	ERNET India's response	Modified Tender clause statement is given belo	W:		
	Modified Tender clause statement	A delay by the bidder in the performance of bidder liable to any or all of the followin security, imposition of liquidated damages, and	g sanctions: forfeiture of its performance		
6.	Tender clause no. & Page	Clause 30.1 of Section-B at	Page 16 & 17		
	Tender clause statement	30. Termination for Convenience 30.1 ERNET India may by written notice sent Purchase Orders, in whole			
		time without mentioning any conditions a with a notice period of one week.			
	Queries sought (in	n \Rightarrow This clause is not acceptable. This may be dispensed with.			
	brief)	⇒ In case above is not possible, it is requested to consider that items which are in pipe line or in transit stage, should be exempted from this clause and termination of convenience should not be applicable in the said situation.			
		 For the clause i.e. 'The payments for the items and services which delivered partially (against the POs) shall not be made', in the even 			
		bidder reserves the right to take ba	ment is not made by ERNET India, the ack such equipment in the condition in T India shall provide full co-operation for		
		- The notice period shall be 60 days	T India shall provide full co-operation for		
			termination clause (or) provide notice of 60		

		days before the termination.		
	ERNET India's	Modified clause is given below:		
	response			
	Modified Tender clause statement	30. Termination for Convenience 30.1 ERNET India may by written notice sent Purchase Orders, in whole or in part (for any item convenience. The notice of termination shall spec convenience, the extent to which performance of Order is terminated, and the date upon which such	cify that termination is for ERNET India's work under the Contract and Purchase	
		The notice period in case of termination for conve	enience shall be 30 days.	
		In case of Termination for convenience, ERNET items and services delivered as per the Purchase (
		- The items and services shall be delivered meeting time guidelines, technical specifications and their acceptance as per the tender.		
		- The items (only hardware) which are in transit stage on the date of written notice of ERNET India for the said termination shall be exempted from this clause, subject to that such items shall get delivered, installed and accepted by ERNET India as per the tender		
(against the POs) shall not be delivered and the payment is the right to take back such eq			vices which will be delivered partially . In this event, if such products are ade by ERNET India, the bidder reserves nt in the condition in which it was rovide full co-operation for the same.	
		In case of remote VSAT AMCs, ERNET India m in whole or in part) at any time without mentionin convenience of ERNET India with a notice period	ng any conditions and as per the	
7.	Tender clause no. & Page		Page 17	
	Tender clause statement	Ownership shall not pass to ERNET India unless and until the system has been delivered, installed, commissioned, operationalized, functional and accepted, in accordance with the terms and conditions of the tender and to the entire satisfaction of ERNET India.		
	Queries sought (in brief)	In the current scenario, the title and risk of loss lies with the bidder in spite of the equipment in ERNET premises where the bidder has no control. Once the ordered items are delivered to ERNET, it has to be the sole responsibility of ERNET. In case of any loss or damage due to theft, flood or any other unavoidable circumstances which are beyond the control of the bidder on ERNET's premises, the loss should be to buyer's account. Thus, change the clause.		
	ERNET India's response	No change in the existing clause. However, bidder is advised that items may be ins equipment.	sured suitably till the acceptance of the	

Section-C

8.	Tender clause no. &	Clause 3.1	Page 20		
	Page				
	Tender clause	If required, ERNET India or its representative	supplier shall either		
	statement	replace the rejected goods or make all alteration	s necessary to meet specification required,		
		free of cost to ERNET India.			
Queries sought (in		\Rightarrow Please clarify on the travel & lodging expen	expenses involved in such inspections, when		
	brief) foreign travel is involved and size of the team for such inspection. The				
		for FAT based on the number of people visiting for FAT. Please include a separation			
		 item in financial bill of material consisting of FAT charges for one person. ⇒ Please change the clause from if required to mandatory or else specify a separate lin 			
	item in commercial for such cost.				
	ERNET India's	A new clause no. 3.2 under Factory Inspection	has been added in Section-C. It is given		

	response	below:			
	Clause 3.2	The expenses on travel, boarding & lodging et of team for such factory inspection may be fro			
		The factory inspection will pertain to only those items whose Manufacturer's Authorization Form (MAF) is mandatorily required. The list of such items are mentione at Annexure—VI at page 97.			
		In case, if any cost comes to bidders for such f its cost in the financial bid as a separate line its the bidders shall be taken for L-1 (lowest bid)	em (s) of Annexure—IV. Its cost quoted by		
9.	Tender clause no. & Page	Clause 6.2	Page 21		
	Tender clause statement	The supply of goods/items ordered should be f (one) shipments unless and until instructed/allowed by ERNET	hipment at the remote site is not allowed		
	Queries sought (in brief)	Requested to provide Full address of sites alon ERNET along with the PO.	-		
	ERNET India's response	Site address will be provided to the bidder eith complete the work as per Time Schedule (as gi on which site address will be provided to the s it is dependent on the site-survey activity. Any readiness and its accountability is mentioned in referred for it.	ven at Annexure-III) will start from the date accessful bidder. Regarding site readiness, delay on account of preparation of site-		
10.	Tender clause no. & Page	Clause 8.2	Page 21		
	Tender clause statement	The bidder would undertake civil works for installation of antenna at remote user sites with non-penetrating mount and IFL cable conduiting from antenna to the IDU. Any other civil work like power cabling, site preparation etc. for commissioning of the VSAT Network sites shall be the responsibility of the ERNET India. Other civil works, like			
	Queries sought (in brief)	 concrete platform, earthing, etc shall be done as per the purchase orders. If the site is not ready within 30 days of supply of equipment, the reason of which is beyond the scope of bidder, The equipment supplied should be deemed as accepted and payment for the same should be released on pro-rata basis. 			
	ERNET India's response	Modified Tender clause statement is given below:			
	Clause 8.2	The bidder would undertake civil works for installation of antenna at remote user sites with non-penetrating mount and IFL cable conduiting from antenna to the IDU. Any other civil work like power cabling, site preparation etc. for commissioning of the VSAT Network sites shall be the responsibility of the ERNET India. Other civil works, like concrete platform, earthing, etc shall be done as per the purchase orders.			
		In case remote VSAT site is not ready within 9 submitted by the bidder at ERNET India (whic commissioning of items is pending due to it, th basis will be released on the request of bidder. than bidder shall install and commission the ite	hever be later) and installation, an the payment of such items on pro-rata But, as and when the site become ready,		
11.	Tender clause no. & Page	Clause 8.13	Page 23		
	Tender clause statement	ERNET India shall, however, have the right to reduce the period of 15 consecutive days, 24 hours a day prescribed for acceptance tests.			
	Queries sought (in brief)	considered.	There should be a fixed time for acceptance. Post that deemed acceptance should be considered.		
10	ERNET India's response	\Rightarrow No change in the tender clause statement			
12.	Tender clause no. & Page	Clause 8.15.2	Page 23		
	Tender clause statement	During the installation and acceptance of network items, adequate number of engineers (for 24x7x365days support)complaints of remote sites and will coordinate to resolve them in stipulated time.			
	Queries sought (in	It is requested that ERNET India to keep the m	anpower requirement as a separate line item		

	brief)	in the Bill of	Material since it comes under serv	vice tax purview. Providing a service under		
		the guise of hardware is against the service tax rules.				
	ERNET India's response	as a separate		ly, the same may be quoted by the bidders cost quoted by the bidders shall be taken		
13.	Tender clause no. & Page	Clause 12	st old) evaluation.	Page 24 to 25		
	Tender clause statement	Payment Te	Payment Terms			
	Queries sought (in brief)	 ⇒ Requested to consider advance payment towards onsite CAMC against 100% BG of equal amount for the period of 3 months. ⇒ Please amend payment terms as "80% payment after delivery of equipment and 20% to be paid after acceptance". ⇒ For inter- state billing WCT deduction is not possible to settled by the bidder or buyer. Hence WCT should not be part of TDS. ⇒ Requested that any additional cost due to increase in govt taxes, will be absorbed by ERNET. ⇒ Request to release the 100% payment against PBG submission to support Indian suppliers too since 100% payment against LC is already there for imported items. It is suggested to keep the same terms with imported as well as indigenous items. As Govt is also encouraging Make In India, so Indigenous products should not be at any disadvantage. 				
	ERNET India's response		arding change in Govt taxes, it is c lified Tender clause statement is gi			
	Modified Tender clause statement	(i) I I I I I I I I I I I I I I I I I I I	to the supplier shall be made in the En case of imported items, the ERNET India through our Banker. o submit the Bank Guarantee (Be Section-B. In case of Rupee Value items: 10 services, etc after their acceptance shall be released subject to the sub- Clause 16 of Section-B and as per On the request of bidder, ERNET of cost of equipments after deliver 3G of total cost of equipment/iter the same shall be extended by the equipments). The bidder shall sub- tems at site (s). Payment towards on-site con Payment towards services like on etc will be released on quarterly period subject to providing satisfa and conditions and meeting SLA.	Letter of Credit would be opened by However, the bidder would be required G-2) as mentioned under Clause 16 of 0% of cost of equipment, accessories, (meeting all tender terms and conditions) mission of BGs (BG-1) as mentioned under		
Sect	ion-E					
14.	Tender clause no. & Page	Clause 2		Page 28		
	Tender clause statement	Bidder must have supplied, installed, maintained and operationalised at least 100 DV ACM, CCM/MFTDMA type VSATs and 10 normal SCPC type VSATs in the count the same type.				

	Queries sought (in brief) ERNET India's response Modified Tender clause statement	Bidder must have experience of Hub operations, Hub maintenance and remote VSAT maintenance of at least one DVB-S2 ACM, CCM/MFTDMA type of VSAT Network in the country of the same type. The Bidder must be engaged in providing above mentioned continuously at least from last one year. Requested that this clause as "The Bidder must be engaged in providing above mentioned continuously at least from last six month." Modified Tender clause statement is given below: Bidder must have supplied, installed, maintained and operationalised at least 100 DVB-S2 ACM, CCM/MFTDMA type VSATs and 10 normal SCPC type VSATs in the country. Bidder must have experience of Hub operations, Hub maintenance and remote VSAT maintenance of at least one DVB-S2 ACM, CCM/MFTDMA type of VSAT Network in the country. The Bidder must be engaged in providing above mentioned continuously at least from last one year.				
15.	Tender clause no. &	Clause 5 Page 28 to 29				
	Page Tender clause statement	A list of purchasers of DVB-S2 ACM, CCM /MFTDMA type VSATs, normal SCPC type VSATs andpartners in the last three years along with quantity must be enclosed. The list must show at supply of at least 500 DVB-S2 ACM, CCM /MFTDMA typein support (mandatory). If this is not provided, the bid stands disqualified.				
	Queries sought (in brief)	Suggested with following change: A list of purchasers of DVB-S2 ACM, CCM /MFTDMA type VSATs, normal SCPC type VSATs and High capacity type VSATs (of the same type which are quoted against this tender) through the Bidder as well as through its OEM or its channel partners in the last three years along with quantity must be enclosed. The list must show at supply of at least 500 DVB-S2 ACM, CCM /MFTDMA type VSATs; 10 normal SCPC types of VSATs and 10 high capacity type VSATs (of the similar type which are quoted against this tender) in the last three years with documentary				
	ERNET India's	proof in support (mandatory). If this is not provided, the bid stands disqualified." Modified Tender clause statement is given below:				
	Modified Tender clause statement	A list of purchasers of DVB-S2 ACM, CCM /MFTDMA type VSATs, normal SCPC type VSATs and High capacity type VSATs (of the same type which are quoted against this tender) through the Bidder or through its OEM or its channel partners in the last three years along with quantity must be enclosed.				
		The list must show supply of at least 500 DVB-S2 ACM, CCM /MFTDMA type VSATs; 10 normal SCPC types of VSATs and 10 high capacity type VSATs (of the same type which are quoted against this tender) in the last three years with documentary proof in support (mandatory). If this is not provided, the bid stands disqualified.				
16.	Tender clause no. & Page	Clause 6 Page 29				
	Tender clause statement Queries sought (in	The annual turnover of the Bidder for the last three years should be a minimum of Rs.100 Crore from Indian Operations (in each year).Requested to amend the annual turnover for last three years to be minimum 50 Crore				
	brief) ERNET India's	from Indian operations (in each year) for better participation.Modified Tender clause statement is given below:				
	response Modified clause	The average annual turnover of the Bidder for the last three years should be a minimum of Rs. 70 Crore from Indian Operations (i.e. total of 3 years divided by 3).				

Sec	tion-F			
7.	Tender clause no. & Page	4 th Paragraph of Clause 6.2	Page 36	
	Tender clause statement	The bidder shall coordinatetender.	applicable within the scope of this	
	Queries sought (in brief)	If there is any statutory reason for the delay or any other reason for delay due to internal operation of DoT, then bidder should not be penalised because bidder's scope is to co- ordinate with DoT. Please issue necessary amendments stating that we will not be penalised for any delay which is beyond bidder's control.		
	ERNET India's response	Please refer clause 23 of Section-B in t Thus, no change in the statement/claus	his regard which explains the query.	
8.	Tender clause no. & Page	Clause 1 of 6.3	Page 36	
	Tender clause statement	connectors, antenna, converters, etc) (f		
	Queries sought (in	- VSAT Hub = Maximum of	six (6) hour from the time of reporting of fault. lays since most of the equipments are old and	
	brief)	mobilisation and suitable fitment takes time and also repair/replacement of items will take time.		
	ERNET India's response	Modified Tender clause statement is given below:		
	Modified Tender clause statement	 connectors, antenna, converters, etc) (falways be in good working and function Network Availability: VSAT Hub = 99.9% (average) Maximum Time To Repair / VSAT Hub = Maximum of the state of the stat	Replace (MTTR): f 48 hours from the time of reporting of fault. given at Annexure-VIII.	
9.	Tender clause no. & Page	Clause 3 of 6.3	Page 37	
	Tender clause statement	 fulfillment of the following performant AMC periods: SCPC VSAT link availability = 9 Maximum Time To Repair (MTT reporting of fault (using redundant) Maximum Time To Repair /Replate SCPC VSAT link (both hub and refault. 	he art technology and network design and guarantee ce parameters during the warranty and subsequent 9.5% (averaged on quarterly basis) R) SCPC VSAT link = 04 hours from the time of t items supplied with VSAT) ice by same make & model (MTTR/Re) of items of emote side) = 24 hours from the time of reporting of	
	Queries sought (in	Should also meet all SLA condition Request to clarify uptime based on Cit		

ERNET India's response	Modified Tender clause statement is given below:
Modified Tender clause statement	For high capacity SCPC VSATs Network
	 The bidder would ensure the state-of-the art technology and network design and guarantee fulfillment of the following performance parameters during the warranty and subsequent AMC periods: SCPC VSAT link availability = 99.5% (averaged on quarterly basis) Maximum Time To Repair (MTTR) SCPC VSAT link = 05 hours from the time of reporting of fault (using redundant items supplied with VSAT) Maximum Time To Repair /Replace by same make & model (MTTR/Re) of items of SCPC VSAT link (both hub and remote side) = 48 hours from the time of reporting of fault. Should also meet all SLA conditions. Note: Please note that sites are located at Port Blair, Kavaratti.

Annexure II-A

20			• `		
20.	Tender clause no. & Page	Clause 1 of 3.0 (of Table)			Page 46
	Tender clause	Outgoing Stream			
	statement	Data Rate:		Capable from 1 (insteps of 300	.5Msps to 35Msps or higher 0ksps or less)
	Queries sought (in brief)	Request ERNET to kindly amend it as 500 Ksps			
	ERNET India's response	Modified Tender clause statement is given below:			
	Modified Tender	Outgoing Stream			
	clause statement	Data Rate:		Capable from 1 (insteps of 500	.5Msps to 35Msps or higher lksps or less)
21.	Tender clause no. & Page	Clause 2 of 3.0 (of Tabl	le)		Page 46 & 48
	Tender clause	Incoming Stream			
	statement	Data rate for Single	From	128Ksps to 2.5N	Asps or higher
		inbound:			east 4 different sizes upto 2.5Msps)
			Note: Size of one inbound shall also support and configurable with 2Watts BUC at VSAT, QPSK 2/3, 1.8M VSAT antenna		SAT, QPSK 2/3, 1.8M VSAT antenna
			with linear polarisation, INSAT-3C C-band parameter as per latest TEC/IR, location A&N, Lakshadweep and N-E states		
		Roll off factor:	1.2 or (20% of	better or better)	
	Queries sought (in brief)	 ⇒ Request to kindly amend Data rate of single inbound as 256 Ksps to 6 Msps. ⇒ Request ERNET to kindly amend Roll off factor as 25% 			
	ERNET India's response	Modified Tender clause statement is given below:			
	Modified Tender	Incoming Stream			
	clause statement	Data rate for Single	From	256Ksps to 2.5N	Asps or higher
		inbound:	(in dif	ferent steps, at le	east 4 different sizes upto 2.5Msps)
					und shall also support and configurable VSAT, QPSK 2/3, 1.8M VSAT antenna
					n, INSAT-3C C-band parameter as per n A&N, Lakshadweep and N-E states. If it
					enalties on the bidder shall be applicable.
		Roll off factor:			
22.	Tender clause no. & Page	2 nd Table of Clause 3.0			Page 48 & 49
	Tender clause	*C-Band to L-Band co	onverter	specs are as be	elow:
	statement	(Note: Other convertsequivalent specs)			

		Input Parameters	Input Frequency	
		Input Farameters		etor : N. Female
		Output	Output Frequency	
		Parameters	Output	
		Other Parameters	Gain : 35 dB ±2dB	
			Voltage : 220±10	
		Others		nnectors, monitoring connectors, etc
			-If system is chassis based	l, it shall have two slots.
	Queries sought (in	Request for the foll	lowing changes meters: Input connector: N	an CMA Famala
	brief)			v: 950 – 1450MHz (500MHz BW) as input
			is 3.7-4.3GHz(500MHz BV	
			ameters: Gain : $35 \text{ dB} \pm 3 \text{dB}$	
	ERNET India's	Modified Tender cl	lause statement is given belo	ow:
	response			
	Modified Tender clause statement		nd converter specs are as b rts if required and supplied	below: by bidder shall also be of same make and
		Input Parameters	Input Frequency : 3.7 to 4	.2GHz
			Input Impedance : 50Ω	
			VSWR <2:1	
				1A, Female (but the bidder shall ensure its
		Output	proper integration with ot Output Frequency : 950 –	
		Parameters	Impedance : 50Ω	1430101112
			VSWR <2:1	
			Output Power @P1dB : +	15dBm minimum
			Output connector : N, Fen	nale
		Other Parameters	Gain : 35 dB ±3dB or bett	
			-	Bc, 0 dBm out; < -60 dBm, signal
			independent	50 ID
			Spurious, Out of Band < -	
				c for two carriers at -10dBm out 5 dB, over frequency band; ±0.5 dB, 40
			MHz BW	5 ub, over frequency band, ± 0.5 ub, ± 0
			Frequency sense : Invertir	າຊ
				01 ppm max over temp internal reference;
			ext. ref. input	
			10MHz In/out level :3dBr	
			Noise Figure : 15 dB at m	inimum attenuation
			Phase Noise :	
			@1KHz <-75dBc/Hz @10KHz <-85dBc/Hz	
			@10KHz < -85dBc/Hz @100KHz < -95dBc/Hz	
			@1MHz < -105dBc/Hz	,
				-
			Voltage : 220±10VAC, 50	
		Others		nnectors, monitoring connectors, etc
23.	Tender clause no. &	Clause 4 of 4.2 (of	-If system is chassis based	Page 52
23.	Page	Clause 4 01 4.2 (01	1 4010)	Tage 52
	Tender clause	IDU		
	statement	RF In Frequency :	950 MHz – 1950 MHz	
		RF Out Frequency	: 950 MHz – 1950 MHz	
		Data Port:No. of Ports :1 Port (minimum)		
		Input data port : Ethernet 10/100 (RJ 45)		
			tocol: TCP/IP, UDP	
		Bit Error Rate:	Better than 1x 10 ⁻⁷	hla ta handla minimum Mhna Tri data sata
				ble to handle minimum 2Mbps Tx data rate
<u> </u>	1	Outbound data rate: Supplied IDU shall be capable for minimum 40Mbps (Rx) download		

		data rata ta ramata VCAT			
		data rate to remote VSAT Transmit mechanism: MF-TDMA			
		Operating Voltage: 100V - 220V AC, 50Hz			
		Relative humidity: 90%			
		IDU should be guaranteed to support at least or more than 10,000 numbers of packets per			
		second (pps).			
		IP features: RIP, DHCP,NAT/PAT, IGMP, IP Prioritization, VLAN, DiffServ, SIP, IPv4			
		and IPv6, Static routing, IP multicast, UDP broadcast support			
		Security: IPSec (end to end), ACL Firewall			
		Mechanical / Environmental /General condition:			
		-Small in size & weight & single box			
		-Operating temperature: 0 degree to +50 degree C			
		-Relative humidity: upto 90%			
	Quarias sought (in	-Indian Power cable			
	Queries sought (in brief)	It is with respect to Outbound data rate: ⇒ The VSAT download speed is licensed-based on data rate size. Thus, initially			
	offer)	license for 10Mbps data rate for VSAT IDU may be taken and later license for			
		higher data rate upto 40Mbps may be purchased on requirement.			
		ingher data rate apro torrops may be parenased on requirement.			
		It is with respect to IP features:			
		\Rightarrow IP Multicast is better and more elegant way to transmit data to a group and			
		selected sites (all the sites) as it is "managed & controlled" and more secure, only			
		the allowed VSATs are able to receive the multicast. Broadcast is achieved by			
		multicast traffic to all remote stations. Thus, requested to remove the ""UDP			
		Broadcast Support" from the requirement."			
	ERNET India's	Modified Tender clause statement is given below:			
	response				
	Modified Tender	IDU			
	clause statement	RF In Frequency : 950 MHz – 1950 MHz			
		RF Out Frequency : 950 MHz – 1950 MHz Data Port:			
		No. of Ports : 1 Port (minimum)			
		Input data port : Ethernet 10/100 (RJ 45)			
		Data Transport Protocol : TCP/IP, UDP			
		Bit Error Rate: Better than 1x 10 ⁻⁷			
		Inbound data rate: Supplied IDU shall be capable to handle minimum 2Mbps Tx data rate			
		Outbound data rate: Supplied IDU shall be capable for minimum 40Mbps (Rx) download			
		data rate to remote VSAT			
		Transmit mechanism: MF-TDMA			
		Operating Voltage: 100V - 220V AC, 50Hz			
		Relative humidity: 90%			
		IDU should be guaranteed to support at least or more than 10,000 numbers of packets per			
		second (pps).			
		IP features: RIP, DHCP, NAT/PAT, IGMP, IP Prioritization, VLAN, DiffServ, SIP, IPv4			
		and IPv6, Static routing, IP multicast			
		Security: IPSec (end to end), ACL Firewall			
		Mechanical / Environmental /General condition:			
		-Small in size & weight & single box			
		-Operating temperature: 0 degree to +50 degree C			
		-Relative humidity: upto 90%			
		-Indian Power cable			
24.	Tender clause no. &	Clause (i) of 6.0 Page 53 & 54			
	Page				
	Tender clause	For DVB-S2 ACM, CCM/MF-TDMA network			
	statement	For one inhound sharped to ff a to U.t. OFC When I the set the set the set to the set the set to the set			
		 For one inbound channel traffic to Hub: 256 Kbps Inbound channel (assume 2Watte BLIC at VS AT) 			
		2Watts BUC at VSAT) For outbound channel troffic, to Romote VSATe: 20Mbps outbound channel			
		• For outbound channel traffic to Remote VSATs: 20Mbps outbound channel Link engineering for the following shall also be provided:			
	l	Link engineering for the following shall also be provided:			

Queries sought (in brief) ERNET India's response	 1 Outbound channel with 36MHz Transponder in saturation 512kbps Inbound channel size One Inbound channel with 512KHz Maximum size of one Inbound channel with 2Watts BUC, 3Watts and 5Watts BUC Note: 1. Take Hub antenna 9.2 M at Bangalore; VSAT antenna of 1.8 M with linear polarization; INSAT-3C, C-band parameters as per latest TEC/IR document of DoT; Rain fade margin; VSAT site location of A&N, Lakshadweep and N-E states. 2. For Outbound channel, take QPSK Modulation and FEC as 3/4 (or worse) 3. For Inbound channel, take QPSK Modulation and FEC as 2/3 (or worse). 4. For VSAT sites located in A&N, Lakshadweep and N-E, 2.4M antenna may be assumed. ⇒ The inbound channel rate are generally in pre-defined Symbol Rate values, So request to change this to 512 Ksps in place of 512 KHz. ⇒ In point no. 1, it is asked to consider 1.8m antenna with VSAT location as A&N, Lakshadweep and N-E, while in point no. 4 it has been asked to consider 2.4m VSAT antenna for the same locations. Thus, please clarify on the VSAT antenna and location to be consider for the Link Budget calculations to be submitted. Modified Tender clause statement is given below:
Modified Tender clause statement	 For DVB-S2 ACM, CCM/MF-TDMA network For one inbound channel traffic to Hub: 256 Kbps Inbound channel (assume 2Watts BUC at VSAT) For outbound channel traffic to Remote VSATs: 20Mbps outbound channel Link engineering for the following shall also be provided: 1 Outbound channel with 36MHz Transponder in saturation 512kbps Inbound channel size One Inbound channel with 512 KHz or with that value of KHz which is nearest to 512 KHz. Maximum size of one Inbound channel with 2Watts BUC, 3Watts and 5Watts BUC (P1dB) Note: Take Hub antenna 9.2 M at Bangalore; VSAT antenna of 1.8 M with linear polarization; INSAT-3C, C-band parameters as per latest TEC/IR document of DoT; Rain fade margin; VSAT site location of UP, MP, Punjab, Uttarakhand, Tamilnadu, Gujrat, West Bengal. For Outbound channel, take QPSK Modulation and FEC as 3/4 (or worse) For Inbound channel, take QPSK Modulation and FEC as 2/3 (or worse). The link engineering for VSAT sites located in A&N, Lakshadweep and N-E with 2.4M antenna shall also be provided.
Tender clause no. & Page	Clause 7(1) Page 54
Tender clause statement	The bidder shall provide training to 2 officers at the manufacturer location in system design and operation and maintenance of the network. The bidder shall provide training material, documents, etc for this training to the officers. The expenses on travel, boarding & lodging etc. shall be borne by ERNET India. Its cost shall be quoted in the bid.
Queries sought (in brief) ERNET India's	There are several OEMs involved in this project. At which equipment's OEM location to be preferred for the training? Also provide the number of days/hours. Modified Tender clause statement is given below:
response Modified Tender clause statement	The bidder shall provide one week training to 2 officers at the manufacturer location (i.e. OEM of DVB-S2 ACM baseband) in system design and operation and maintenance of the network. The bidder shall provide training material, documents, etc for this training to the officers. The expenses on travel, boarding & lodging etc. shall be borne by ERNET India. The cost of training shall be quoted in the bid.

Anr	nexure-II-B						
26.	Tender clause no. & Page	Clause	e 2 (iv)		Page 55		
	Tender clause statement	data ra	ate from each VSAT shal	l be maximum of			
	Queries sought (in brief)	3.8Mt	r/4.5Mtr antenna, kindly	provide the corre	n operate of 4.5MHz/8MHz on a ect DR as per TEC/DOT doc.		
	ERNET India's response	2. In 0 3. A	013. n above clause, Data rate f star network).	limit is 8MHz w 4Mbps of data ra	C document no. TEC/IR/SCB-08/03.OCT ith 3.8meter C-band antenna size (in case te from Remote Tx may be achieved and TEC document		
27.	Tender clause no. & Page	Clause			Page 58		
	Tender clause statement	the va	rious units/sub assembles		f equipment alarms of		
	Queries sought (in brief) ERNET India's		ested to be remove this.				
	response Modified Tender		ied Tender clause statem	-	w: f equipment and link performance, alarms,		
	clause statement	contro perfor	ls and monitoring faciliti	es shall be provid	ded. In case of fault and degraded fault based on alarm & monitoring		
28.	Tender clause no. & Page		e 1 (a) of 7 (of Table for	SCPC	Page 58		
	Tender clause	a)	General Specifications				
	statement		Symbol Rate Range		sps to 25 Msps in 1 ksps steps		
	Queries sought (in	Does t	Does the bidder need to enable the modem with 25Msps feature from the date of supply?				
	brief)	Please	confirm. Also, please cla	arify if this is Ms	ps or Mbps?		
	ERNET India's response	It is re	equired from day 1. It is s	ymbol rate.			
29.	Tender clause no. & Page		e 1 (b) of 7 (of Table for s	SCPC Modem)	Page 59		
	Tender clause	b)	Modulator (Dual IF)	I			
	statement		L-Band Monitor	dB	d or 900 + 70/140 MHz IF at - 27dBm ± 3		
			Quadrature PhaseSideband 35 dB below unmodulated carrierError and AmplitudeImbalance				
	Queries sought (in brief)	 ⇒ L-band monitoring is not required, as some OEMs have built-in receive signal level monitoring in the modem. Thereby, it would make L-band monitoring unnecessary depending on what requires to be achieved. Alternatively, an External coupler can be used for monitoring of L –band. (Integrator's responsibility). ⇒ Quadrature Phase Error and Amplitude Imbalance shall be 'Sideband 30 dB below unmodulated carrier' 					
	ERNET India's	Modif	ied Tender clause statem	ent is given belov	w:		
	response	1					
	Modified Tender	b)	Modulator (Dual IF)	a vo			
	clause statement		L-Band Monitor	dB (or) Extern	d or $900 + 70/140$ MHz IF at $- 27$ dBm ± 3 al coupler shall be used for monitoring of shall be the bidder's responsibility.		

			Quadrature Phase Error and Amplitude Imbalance	Sideband 30 dI	3 or better below unmodulated carrier
30.	Tender clause no. & Page	Clause	e 1 (d) of 7 (of Table for	SCPC Modem)	Page 59
	Tender clause	d)	Basic Unit Connectors		
	statement		L-Band Monitor	SMA female	
			Data Interfaces		00/1000Base-T Ethernet both IPv4 and IPv6 for their full
	Queries sought (in brief)	t ⇒]	feature and pertains to a c	certain OEM. oth IPv4 and IPv6	or as an option since it is not a necessary
	ERNET India's response		ied Tender clause statem		w:
	Modified Tender	d)	Basic Unit Connectors	-	
	clause statement		L-Band Monitor	the items quote integration and functioning).	t is optional, but the bidder shall ensure that d shall have all required connectors for VSAT link commissioning and
			Data Interfaces	2 x RJ-45 10/1 -Shall support functionality. (Note:	00/1000Base-T Ethernet both IPv4 and IPv6 for their full
				of OE tender to quo that O	
				moder featur moder shall u IPv4 a rate co applic	in this tender, if any bidder quote the m supporting both IPv4 & IPv6 (dual) es, than the bidder who has quoted the m with only IPv4 support, than the bidder upgrade the supplied modems with dual & IPv6 feature within one year from the pontract date, otherwise all penalties will be able. All types of cost for such upgradation be born by the bidder.)
31.	Tender clause no. &		e 3 (a) of 7 (of Table for)		Page 60
	Page Tender clause	a)	atts(P1dB)) General It	is a single inter	ated unit with built-in AC power supply.
	statement	<i>a)</i>	T V cu sy	he unit has built- ital parameters li urrent etc will be ystem maintainab	in data logging up to 30 days. ke Temp, Output power mute status, LNB recorded at time stamped interval for ility
				The unit has a phase noise performance which meets or exceeds IESS-308/309 standard	
					st M&C, Ethernet for monitoring
					P and web interface login for M&C
			di ar	isconnected and r mplifier	ration, faulted online unit may be eplaced without affecting online power
			Т	he supports Indu	stry standard FSK communication
			01		ent protection against open/short on the Tx ans of an inbuilt Output Isolator present
	Queries sought (in brief)		equested to amend as 40	events, alarms or	ly. Parameters like Temp, Output power orded in the BUC. However, it can be

						onding commands at regular time intervals.
						d. Since we have Ethernet it does not make
	ERNET India's		v sense to have FSK. ed Tender clause stat			
	response	Wiodini	ed Tender clause sta	tement is giv		10 w.
	Modified Tender	a)	General	It is a sing	le inte	grated unit with built-in AC power supply.
	clause statement	ŕ				t-in data logging up to 30 events or 30 days
				for alarms.	•	
				Darameters	e lika 1	Femp, Output power mute status, LNB
						be recorded in the computer through
						gular interval of times for system
						or same may be maintained in the BUC itself.
						hase noise performance which meets or 08/309 standard
				The unit ha	as at le	east M&C, Ethernet for monitoring
						MP and web interface login for M&C
						peration, faulted online unit may be
				amplifier		I replaced without affecting online power
						erent protection against open/short on the Tx
				inside the		eans of an inbuilt Output Isolator present
32.	Tender clause no. & Page		3 (b) of 7 (of Table t tts(P1dB))	for BUC-		Page 60
	Tender clause	b)	RF features			
	statement		Output Frequency			50 MHz
			Available power	51	dBm ((125 W)
			Output @ P1 dB	CD	01070	
			Output Connector		$\frac{R137G}{1 \text{ dB}}$	or suitable
			Output Return Los Gain Linear		dB mir	2
			Adjust			0.5 dB step
			Gain flatness			full Band or better
			Gain variation ove	er +/-	1.5 dB	or better
			temp -40 to +55 D			
	Queries sought (in brief)	-	ted to amend "Outpu			
	ERNET India's response	Modified Tender clause statement is given below:				
	Modified Tender	b)	RF features			
	clause statement		Output Frequency			50 MHz
			Available power Output @ P1 dB	51	aBm ((125 W)
			Output Connector	CPI	R137G	or suitable
			Output Return Los			VSWR : 1.3:1
			Gain Linear	70 0	dB mir	1
			Adjust	20 0	dB in (0.5 dB step
			Gain flatness			full Band or better
			Gain variation ove temp -40 to +55 D		1.5 dB	or better
33.	Tender clause no. & Page		3 (e) of 7 (of Table tts(P1dB))			Page 61
	Tender clause	e)	Internal reference	e		
	statement	Í	Freq		MHz o	over range of -5 to +5 dBm
	satement		Frequency stability)E-10 / day
			Frequency stability $\pm/-5 \times 10E-107$ dayRequested to amend Frequency stability as $\pm 2 \times 10-9$ /day.			
	Queries sought (in brief)	Reques				2 x10-9/day.
	Queries sought (in brief) ERNET India's	-		ency stabilit	± 2 y as ± 2	-

	Modified Tender	e)	Internal ref	erence		
	clause statement		Freq		10 MHz c	over range of -5 to +5 dBm
			Frequency st	ability		day or better
34.	Tender clause no. &	Clau	se 7 of 7 (of Tabl			Page 61 & 62
	Page		h for BUC and L		, , , , , , , , , , , , , , , , , , ,	C .
	Tender clause	Gene	ral	- 1:1 BUC	and LNB r	edundancy switch, suitable for the supplied
	statement					note site setup
				- All cable	es, connecto	rs, splitters/combiners, mounting kits,
						ed for their integration and installation
	Queries sought (in				al switch for	r 1:1 configuration if it is inbuilt available
	brief)		BUC? Please co			
	ERNET India's	Yes,	the bidder needs	to quote it.	Thus, no cha	ange in the clause.
	response					
35.	Tender clause no. &		se 11(a) & (b) &			Page 65 to 67
	Page		Noptimizer at Ce	ntral site for		
			nmetric link)			
	Tender clause	a)	Generic			l provide TCP (Transmission Control
	statement		Requirement			h, header compression, data compression,
						and dynamic content caching to achieve
				optimizati		Duidas and Davida davida
						n Bridge and Routed mode load compression, packet aggregation, TCP
					on and object	1 1 00 0
						ndergo header compression
						w levels (2 or more) of settable hierarchical
				QoS.	provide lev	w levels (2 of more) of settable metachical
				-	vork in a po	int to point topology.
						oth IPv4 and IPv6 and mixed environment.
		b)	Functional &			d provide the following features:
		0)	Technical			pression of HTTP traffic, file attachments,
			Requirement			and downloads
			1			n of all HTTP cookies, HTTP header and
						d post in both directions
						tion and smoothing
				• I	Dynamic obj	ect and file caching
						a suppression
						sistent connection between sites.
						on ingress side
				-	ed traffic sh	ould be aggregated into larger Ethernet
				packet		
						ould be configurable based upon maximum
						aximum size of aggregation.
						on and smoothing should reduce the amount
						present the image, without significantly
						ception of the image.
						have user configurable setting to select
						age and size
						d have static caching abilities. d also support intelligent cache differencing
						1 support data de-duplication
						d support IEEE 802.1Q (VLAN) traffic.
						ald support adding/deletion of IEEE802.1q
				VLAN tag		nd support adding/deletion of hele802.14
						l support flow control in compliance with
				IEEE802.		a support now control in compliance with
						d support source IP preservation.
						d support at least 10,000 accelerated session
				(connection		a support at reast 10,000 according session
					,	l have minimum 12GB RAM.
						d be 19" rack mountable
L		1		ine equip	ment should	

Participant Provide "fail to wire" capability with at least one pair of bypass port. The fail to wire should frigger under two conditions, a) active flow exceeds max configured, b) loss of powerbox failure relationation. The capipment should also provide the feature of 1+1 system level relationation. The equipment should also provide the feature of 1+1 system level relationation. The equipment should also provide the feature of 1+1 system level relationation. The equipment should be able to support Strict Priority(SP) queue and Stochastic Fair weighted queue(SFW) at the egree WAN interface. The capipment should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). Ta should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). The should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). Queries sought (in beite) Request to either remove it or make it an optional feature or more generic. brief) Queries sought (in requirement Nodified Tender classe statement is given below: response Response Nodified Tender classe statement is given below: response. I should work with hould provide TCP (Transmission Control Protoco) acceleration, and object caching. Protocol acceleration and object and flidge and Routed mode. I shouid work with houl IP shall to back aggregation. TCP acceleration				
Image: Second				The equipment should have a minimum 1TB of Hard disk capacity
Queries sought (in brief) Request to either remove i or make it an optional forwide TCP (Transmission Control) Protocol and dynamic content and dynamic content caching to achieve optimization Queries sought (in brief) Request to either remove i or make it an optional forwide TCP (Transmission Control) Protocol and dynamic content and dynamic content caching to alther requirement 0) Functional & The equipment should provide TCP (Transmission Control) Protocol and dynamic content caching to alther response 0) Others Installation, commissioning and integration of the system with the existing setup of ENR-TI India Hub and/or at ERNET India use sites. 1/2 Others Installation, commissioning and integration of the system with the existing setup of ENR-TI India Hub and/or at ERNET India use sites. 0) General requirement The equipment should provide TCP (Transmission Control) Protocol) acceleration, header compression, data compression, it should work in a point to point optional caching to achieve optimization 10) Functional & Technical Requirement The equipment should provide TCP (Transmission Control) Protocol) acceleration and dynamic content caching to achieve optimization 11 should work in a boint to point topology. It should work in a point topology. 12 should work in a point topology. It should work in a point topology. 13 should work in a point topoint oplay and compression difter transfire classtifterat				
exceeds max configured, b) loss of powerhox failure The equipment should also provide the feature of 1+1 system level The equipment should support traffic classification on the basis of the following: The equipment should be able to support Strict Priority(SP) queue and Stochastic Fair weighted queue(SFW) at the egree WAN interface It should provide a throughput of 60Mbps (this equipment will be installed a central site with asymmetric link). It should provide a transition, commissioning and integration of the system with the existing setup of ERNFT India Hub and/or at ERNFT India user sites. All cubles, connectors, et to install and commission the equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic control. Protocol) acceleration, header compression, data compression, image transformation and dynamic control caching to ablive optimization Modified Tender ai General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic control caching to ablive optimization b) Functional & Technical & Technical & Technical & Technical & Technical & Technical & Technical & Technical & The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, integr transformation and dynamic control caching to ablive optimization b) Functional & Technical & Technical & Technical & Technical & The equipment should provide TCP (Transmission Control Protocol) acceleration and dynamic control caching to ablive optimization b) <				
Particle Particle The equipment should also provide the feature of 1+1 system level redundancy. The equipment should support traffic classification on the basis of the following: • IP Subnet • IP Subnet • VLAN tag • Port The equipment should be able to support Strict Priority(SP) queue and Stochastic Fair weighted queue(SFW) at the egree WAN interface g) Others Installed are central site with asymmetric link). It should provide a least 30,000 PPS Installed are central site with asymmetric link). It should provide a least 30,000 PPS Installed are central site with asymmetric link). It should provide a least 30,000 PPS Installation, commissioning and integration of the system with the existing setup of ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Portocolo Acceleration, header compression, data compression, and provide traffic Priority CPC Transmission Control Provide TCP (Transmission Control Provide CPC Provide TCP (Transmission Control Provide payload compression, and and ynamic content acching to achieve optimization. It should provide few levels (2 or more) of settable hierarchical Question and object caching. It should work with both IPv4 and IPv6 and Imized and environment. It control as the obid frequence and HTTP get and post in both directions I should work with both IPv4 and IPv6 and Imized antroical Question and object caching.				
Image: Instant of the set of the				
Image: Construction of the sequence of the sequ				
b Functional Functional IP Subact interface IP Subact VLAN tag It should provide a throughput of 60Mbps (this cupiment will be installed a central size with asymetric link). Interface g) Others Installation, commissioning and inegration of the system with the existing setup of FRNFT India Hub and/or at ERNFT India user sizes. All cables, connectors, etc to install and commission the equipment should provide at least 350,000 PPS Users Installation, commissioning and inegration of the system with the existing setup of FRNFT India Hub and/or at ERNFT India user sizes. All cables, connectors, etc to install and commission the equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization Modified Tender a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should work in a point to point topology. It should work in a point topology. It should work with and provide feel resting. It should work in a point topology. It should work with and Prova and Pixe and Pi				
e Protection e Port The sequipment should he able to support Strict Priority(SP) queue and Stochastic Fair weighted queue(SFW) at the egree WAN interface 1 Histould provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). 1 Histould provide at throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). 1 Histould provide at the ads 350.000 PPS g) Others Installation, commissioning and integration of the system with the existing setup of ERNET India Hub and/or at ERNET India user sites. All cables, connectors, ctr to install and commission the equipment shall be included. Portice Processory Wodified Tender clause statement is given below: The equipment should provide TCP (Transmission Control Propose) Modified Tender clause statement is given below: The equipment should provide TCP (Transmission Control Propose) Modified Tender clause statement is given below: The equipment should provide the clause state aggregation, TCP acceleration and object caching. It should work in both Bridge and Routed mode It should work in both Bridge and Routed mode It should work in a point to point topology. It should work with both IPV4 and IPV5 and mixed environment. It should work in a point topology. It should work with both IPV4 and IPV5 and mixed environment.				
9 • VLAN tag • Port The equipment should be able to support Strict Priority(SP) queue and Stochastic Fair verighted queue(SFW) at the egree WAN interface 1 It should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). 1 It should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). 1 It should provide at least 350,000 PPS 9 Others It should provide at least 350,000 PPS 1 It cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. 1 It cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. 1 It should provide TCP (Transmission Control requirement requirement should provide TCP (Transmission, data compression, image transformation and dynamic content caching to achieve optimization 1 It should provide few levels (2 or more) of settable hierarchical Qos. 2 It should work in a point to point topology. 1 It should work in a point to point topology. 1 It should work in a point to point topology. 1				6
e Port The equipment should be able to support Strict Priority(SP) queue and Stochastic Fair weighted queue(SFW) at the egreee WAN interface It should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). It should provide at least 350,000 PPS g) Others g) Others l) Installation, commissioning and integration of the system with the existing setup of ERNET India Hub and/or at ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. histing setup of ERNET India's response. Modified Tender clause statement a) General requirement a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization b) Functional & Functional & Requirement The sould work in both Bridge and Routed mode It should work in both Bridge and Prod and mixed environment. The should work in both Bridge and Routed mode It should work in both directions b) Functional & Requirement The equipment should provide file vells (2 or more) of settable hierarchical QoS. It should work in a point to point topology. The should work in both Bridge and Routed mixed environment. The outpression of all HTTP cookies, HTTP header and HTTP get and post in both dire				
Image: State of the s				
and Stochastic Fair weighted queue(SFW) at the egreee WAN interface It should provide a throughput of 60Mbps (this equipment will be installed at central site with asymmetric link). It should provide at least 350,000 PPS g) Others Installation, commissioning and integration of the system with the existing setup of ERNET India Hub and/or at ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. ERNET India's response Modified Tender clause statement is given below: response General diage transformation and dynamic content caching to achieve optimization requirement a) b) Functional & b) Functional & b) Functional & clause statement b) b) Functional & clause statement Te should work in both Bridge and Routed mode It should work in both Bridge and Provide features: is should work in a point to pology. It should work in both Bridge and Routed mixed environment. b) Functional & compression of HTTP traffic, file attachments, file uploads and downloads compression of HTTP traffic, file att				
Image: state of the source				
g) Others It should provide a theousphur of 60Mps (this equipment will be installed at central site with asymmetric link). g) Others It should provide a tleast 350,000 PPS g) Others Installation, commissioning and integration of the system with the existing setup of EKNET India Hub and/or at ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Oueries sought (in brich) BRNET India's Modified Tender clause statement is given below: response Modified Tender clause statement is given below: response All cables, connectors, etc to install and commission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work in a point to point topology. It should work with both PV4 and IPV6 and mixed environment. b) Functional & Te equipment should provide the following features: ii usbould work in a point to point topology. It should work with both PV4 and IPV6 and Mixed environment. b) Functional & Te equipment should be configurable based upon maximum aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Compresseston of all HTTP cockies, HTTP header and HTT				
g) Others installat at central site with asymmetric link). It should provide at least 350,000 PPS g) Others Installation, commissioning and integration of the system with the existing setup of ERNET India Hub and/or at ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in bried) Request to either remove it or make it an optional feature or more generic. bried) ERNET India's response Modified Tender clause statement is given below: response Modified Tender clause statement a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point topology. It should work with both IPV4 and IPV6 and mixed environment. b) Functional & Technical Requirement b) Functional & Technical Requirement c) Functional & Technical Requirement c) Functional & Technical Requirement b) Functional & Technical Requirement c) Functional & Technical Requirement c) Functional & Technical Requirement c) Functional & Te				
g) Others It should provide at least 350,000 PPS g) Others Installation, commissioning and integration of the system with the custisting setup of ERNET India user sites. All cables, connectors, et to install and commission the cupiment shall be included. Queries sought (in briel) FRNET India's Request to either remove it or make it an optional feature or more generic. briel) Modified Tender clause statement is given below: response a) General requirement requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should work in both Bridge and Routed mode It should work in a point to point topology. It should work in a point to point topology. It should work in a point topology. It should work and should provide the following features: • Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching • Image reduction and smoothing • Dynamic object and file caching • Prancical & Requirement • Compression of all HTTP cookies, HTTP header and HTTP get and postin both directions				
g) Others Installation, commissioning and integration of the system with the existing setup of ERNET India Hab and/or at ERNET India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. brief) ERNET India's response Modified Tender clause statement is given below: Clause statement a) General requirement should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. b) Functional & Technical Requirement The equipment should provide to point topology. t should work with both HP4 and IPv6 and mixed environment. It should work with both dried caching • Losanic object and file caching • Dynamic data suppression • Maintain persistent connection between sites. • Traffic elassification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size. Traffic elassification on ingress side Compressed traffic should be configurable setting to select between quality of image and size. • The equipment should have static caching abilities. • The equipment should have static caching abilities. <td></td> <td></td> <td></td> <td></td>				
existing setup of ERNET India Hub and/or at ERNÉT India user sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. BENET India's response Modified Tender clause statement is given below: response a) General requirement requirement General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. The equipment should provide the lolowing features: • b) Functional & Technical Requirement The equipment should provide the lolowing features: • Lossless compression of HTPP traffic, file attachments, file uploads and downloads • • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image relaying relaying the visual precision. • Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching		g)	Others	
Sites. All cables, connectors, etc to install and commission the equipment shall be included. Queries sought (in brief) Request to either remove it or make it an optional feature or more generic. ERNET India's Modified Tender clause statement is given below: response General Modified Tender a) General The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should work in a point to point opology. It should work in a point to point topology. It should work with both PV4 and PV6 and mixed environment. b) Functional & Technical Requirement The equipment should provide the following features: • Compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP gt and post in both directions • Image reduction and smoothing • Dynamic object asynession • Traffic classification on ingress side • Dynamic object asynession • Traffic classification on ingress side • Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation. Insert comparison should be configurable based upon maximum aggregation time or maximum size of aggregation. • Traffic clasol supportsion of al		0,		
Image of the sought (in brief) Request to either remove it or make it an optional feature or more generic. Bodified Tender clause statement is given below: response Modified Tender clause statement a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Tcchnical Requirement The equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Dynamic object and file caching • Dynamic object and file caching • Dynamic object on figurable based upon maximum aggregation time or maximum size of aggregation. Image reduction and smoothing Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching •				
Image of the sought (in brief) Request to either remove it or make it an optional feature or more generic. Bodified Tender clause statement is given below: response Modified Tender clause statement a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Tcchnical Requirement The equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Dynamic object and file caching • Dynamic object and file caching • Dynamic object on figurable based upon maximum aggregation time or maximum size of aggregation. Image reduction and smoothing Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching •				All cables, connectors, etc to install and commission the
brief) Modified Tender clause statement is given below: response Requirement a) General requirement requirement a) General clause statement The equipment should provide TCP (Transmission Control Protoco) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Technical Requirement Requirement The equipment should provide the following features: • Lossless compression of HTTP raffic, file attachments, file uploads and downloads • Compression of all HTTP cockies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic object and file caching • Dynamic object and file caching • Dynamic object and file caching • Dynamic data suppression • Maintain persistent connection between sites. Traffic classification on ingress side Com				equipment shall be included.
ERNET India's response Modified Tender clause statement is given below: Modified Tender clause statement a) General requirement The equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should work in both Bridge and Routed mode It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. b) Functional & Technical Requirement The equipment should provide the following features: Lossless compression of HTTP traffic, file attachments, file uploads and downodads c Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing b) Functional & Traffic classification on ingress side Opamaric object and file caching c Dynamic object and file caching Dynamic object and file caching b) Traffic classification on ingress side C Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable based upon maximum aggregation tine or present the image, without significantly	Queries sought (in	Requ	est to either remo	ove it or make it an optional feature or more generic.
response The equipment should provide TCP (Transmission Control clause statement a) General requirement The equipment should provide TCP (Transmission Control on transmission control caching to achieve optimization and dynamic content caching to achieve optimization. It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should work in a point to point topology. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. The equipment should provide the following features: b) Functional & Technical Requirement The equipment should provide the following features: It should work with both IPv4 and IPv6 and mixed environment. The equipment should provide the following features: It should work with both IPv4 and IPv6 and mixed environment. The equipment should provide the following features: It should work with both IPv4 and IPv6 and mixed environment. The equipment should provide the following features: It should and downloads Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic data suppression Image reduction and smoothing Dynamic data suppression Image quality reduction and smoothing should reduce the amount of data required to represent the image. <tr< td=""><td></td><td>_</td><td></td><td>-</td></tr<>		_		-
Modified Tender clause statementa)General requirementThe equipment should provide TCP (Transmission Control Protocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed modeIt should work in both Bridge and Routed modeIt should provide payload compression, packet aggregation, TCP acceleration and object caching.b)Functional & Technical RequirementThe equipment should provide few levels (2 or more) of settable hierarchical QoS.b)Functional & Technical RequirementThe equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic object and file caching • Dynamic data suppressionTraffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packetPacket aggregation time or maximum size of aggregation.Traffic classification on smoothing should reduce the amount of data required to represent the image, The equipment should have static caching abilities. The equipment should have static caching abilities. The equipment should have static caching abilities.	ERNET India's	Modi	ified Tender claus	se statement is given below:
clause statementrequirementProtocol) acceleration, header compression, data compression, image transformation and dynamic content caching to achieve optimization It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching.It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work with both Pv4 and IPv6 and mixed environment.b)Functional & Technical RequirementThe equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic object and file caching • Dynamic object and file caching • Dynamic data suppression • Maintain persistent connection between sites.Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing suppression • Dynamic data suppression • Maintain persistent connection between sites.Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image.The equipment should have user configurable based upon tracting the visual perception of the image.The equipment should have user configurable setting to select between quality of image and size The equipment should also support intelligent cache differencing				
b) Functional & Technical Requirement b) Functional & Technical Requirement c) The equipment should provide the following features: Lossless compression of HTTP traffic, file attachments, file uploads and downloads c) The equipment should provide the following features: Lossless compression of HTTP traffic, file attachments, file uploads and downloads c) The equipment should provide the following features: Lossless compression of all HTTP cookies, HTTP header and HTTP get and post in both directions c) Image reduction and smoothing b) Pynamic object and file caching c) Dynamic data suppression main persistent connection between sites. Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable based upon maximum aggregation time or maximum size of aggregation. Image quality of image and		a)		
b) Functional & Technical Requirement c) Technical The equipment should provide the following features: Compression of HTTP traffic, file attachments, file uploads and downloads c) Compression of HTTP traffic, file attachments, file uploads and downloads c) Dynamic data suppression Minitain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image. The equipment should have user configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should have static caching abilities. The equipment should have static caching abilities. The equipment should have static	clause statement		requirement	
It should work in both Bridge and Routed mode It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. Technical Requirement B) Functional & The equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic data suppression • Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image. The equipment should have static caching abilities. The equipment should have static caching abilities.				
It should provide payload compression, packet aggregation, TCP acceleration and object caching. It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Technical Requirement Requirement The equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic data suppression • Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should have support intelligent cache differencing				
acceleration and object caching. It should provide few levels (2 or more) of settable hierarchical QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Technical Requirement Technical Requirement The equipment should provide the following features: • Lossless compression of HTTP traffic, file attachments, file uploads and downloads • Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions • Image reduction and smoothing • Dynamic object and file caching • Dynamic data suppression • Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should have static caching abilities.				
b) Functional & Technical Requirement b) Functional & Technical Requirement b) Functional & Technical Requirement c) Functional & Technical Requirement b) Functional & Technical Requirement c) The equipment should provide the following features: Technical Requirement c) The equipment should provide the following features: Technical Requirement c) The equipment should provide the following features: Technical Requirement c) Lossless compression of HTTP traffic, file attachments, file uploads and downloads c) Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions c) Image reduction and smoothing c) Dynamic object and file caching c) Dynamic data suppression maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. mage quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have static caching abilities.				
QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Technical Requirement b) Functional & Technical Requirement compression of HTTP traffic, file attachments, file uploads and downloads compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have usatic caching abilities. The equipment should have static caching abilities.				acceleration and object caching.
QoS. It should work in a point to point topology. It should work with both IPv4 and IPv6 and mixed environment. b) Functional & Technical Requirement b) Functional & Technical Requirement compression of HTTP traffic, file attachments, file uploads and downloads compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have usatic caching abilities. The equipment should have static caching abilities.				It should arouid for lough (2 or more) of orthold his muchical
It should work in a point to point topology.It should work with both IPv4 and IPv6 and mixed environment.b)Functional & Technical RequirementThe equipment should provide the following features: Lossless compression of HTTP traffic, file attachments, file uploads and downloadsCompression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites.Traffic classification on ingress sideCompressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should have static caching abilities.				· · · · · · · · · · · · · · · · · · ·
b)Functional & Technical RequirementThe equipment should provide the following features: 				
b)Functional & Technical RequirementThe equipment should provide the following features: Lossless compression of HTTP traffic, file attachments, file uploads and downloads Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites.Traffic classification on ingress side Compressed traffic should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities.				
 Technical Requirement Lossless compression of HTTP traffic, file attachments, file uploads and downloads Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image. The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 		b)	Eurotional &	
Requirementfile uploads and downloadsCompression of all HTTP cookies, HTTP header and HTTP get and post in both directionsImage reduction and smoothingDynamic object and file cachingDynamic data suppressionMaintain persistent connection between sites.Traffic classification on ingress sideCompressed traffic should be aggregated into larger Ethernet packetPacket aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should also support intelligent cache differencing		0)		
 Compression of all HTTP cookies, HTTP header and HTTP get and post in both directions Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 				
HTTP get and post in both directionsImage reduction and smoothingDynamic object and file cachingDynamic object and file cachingDynamic data suppressionMaintain persistent connection between sites.Traffic classification on ingress sideCompressed traffic should be aggregated into larger Ethernet packetPacket aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should also support intelligent cache differencing			Requirement	
 Image reduction and smoothing Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 				
 Dynamic object and file caching Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 				
 Dynamic data suppression Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 				
 Maintain persistent connection between sites. Traffic classification on ingress side Compressed traffic should be aggregated into larger Ethernet packet Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation. Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing 				
Compressed traffic should be aggregated into larger Ethernet packetPacket aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should also support intelligent cache differencing				
packetPacket aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should also support intelligent cache differencing				Traffic classification on ingress side
Packet aggregation should be configurable based upon maximum aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should have static caching abilities.				Compressed traffic should be aggregated into larger Ethernet
aggregation time or maximum size of aggregation.Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should have static caching abilities.				*
Image quality reduction and smoothing should reduce the amount of data required to represent the image, without significantly altering the visual perception of the image.The equipment should have user configurable setting to select between quality of image and sizeThe equipment should have static caching abilities.The equipment should have static caching abilities.				
of data required to represent the image, without significantly altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing				
altering the visual perception of the image. The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing				
The equipment should have user configurable setting to select between quality of image and size The equipment should have static caching abilities. The equipment should also support intelligent cache differencing				
between quality of image and sizeThe equipment should have static caching abilities.The equipment should also support intelligent cache differencing				
The equipment should have static caching abilities. The equipment should also support intelligent cache differencing				
The equipment should also support intelligent cache differencing				
The equipment should support data de-duplication				The equipment should support data de-duplication

			The equipment should support IEEE 802.1Q (VLAN) traffic.
			The equipment should support adding/deletion of IEEE802.1q
			VLAN tag.
			The equipment should support flow control in compliance with
			IEEE802.3x.
			The equipment should support source IP preservation.
			The equipment should support at least 10,000 accelerated session
			(connections)
			The equipment should have minimum 12GB RAM.
			The equipment should be 19" rack mountable
			The equipment should have a minimum 1TB of Hard disk (or
			better type) capacity
			The equipment should provide "fail to wire" capability with at
			least one pair of bypass port.
			The fail to wire should trigger under two conditions, a) active
			flow exceeds max configured, b) loss of power/box failure
			The equipment should also provide the feature of 1+1
			redundancy.
			The equipment should support traffic classification on the basis
			of the following:
			IP Subnet
			 VLAN tag
			Port
			It should provide a throughput of 60Mbps (this equipment will be
			installed at central site with asymmetric link).
			It should provide at least 350,000 PPS
	g)	Others	Installation, commissioning and integration of the system with
			the existing setup of ERNET India Hub and/or at ERNET India
			user sites.
			All cables, connectors, etc to install and commission the
			equipment shall be included.

Annexure-II-C

36.	Tender clause no. &	Clause	e 1(a) & (b) of 5 (of '	Table for SCPC Page 70 & 71		
	Page		n: L-Band (For VSA	6		
	Tender clause	a)	General Specificat	tions		
	statement		FEC	Viterbi/ Trellis Coded Modulation (TCM)/ Reed-Solomon		
				(RS)/ Turbo Product Code (TPC)		
			Input /Output	Serial Port for connectivity with router (as per router specs		
			Data Interfaces	which are given in this tender)		
				10/100Base-T Ethernet (optional)		
				IPv4 and IPv6 dual stack full functionality support		
		b)	Modulator			
			Output power	Tx output power range of 25dB, in 0.1dB steps		
	Queries sought (in		FEC:			
	brief)	L)	LDPC may be con	nsidered instead of TPC, sine LDPC is more efficient.		
		For	Input/ Output Data I	Interference		
			1 1	mentioned, whether V.35 or else. Whether a Winchester pig tail		
			1	with Modem to be clarified.		
		⇒		t for both IPv4 and IPv6, requested this to be changed to "IPv4		
			full functionality support"			
		For Modulator: Output Power				
		¢		range mentioned as "25dB, in 0.1dB steps" Should be mentioned dB steps" which is the standard followed by most of the		

			OEMs."			
	ERNET India's response	Modif	-	tement is given below:		
	Modified Tender	a)				
	clause statement		FEC	Viterbi/ Trellis Coded Modulation (TCM)/ Reed-Solomon (RS)/ Turbo Product Code (TPC) / LDPC		
			Input /Output Data Interfaces	Serial Port for connectivity with router (as per router which is quoted by the bidder in this tender) or suitable port which shall connect to the router quoted in this tender.		
				10/100Base-T Ethernet (optional)		
				IPv4 and IPv6 dual stack full functionality support		
				(Note:		
				 If IPv6 support & feature is not available in any of OEM's existing product which meets the tender specs, only than bidder shall have option to quote the items with IPv4 support & feature of that OEM. 		
				 Also, in this tender, if any bidder quote the modem supporting both IPv4 & IPv6 (dual) features, than the bidder who has quoted the modem with only IPv4 support, than the bidder shall upgrade the supplied modems with dual IPv4 & IPv6 feature within one year from the rate contract date, otherwise all penalties will be applicable. All types of cost for 		
				such upgradation shall be born by the bidder.)		
		b)	Modulator			
			Output power	Tx output power range of -25dB, in 0.1dB steps		
37.	Tender clause no. & Page		2(a) & (b) of 5 (of T n: IF-Band (for Hub			
	Tender clause	a)	General Specificati			
	statement		Input /Output Data Interfaces			
				10/100Base-T Ethernet (optional)		
				IPv4 and IPv6 dual stack full functionality support		
		b)	Modulator			
	Queries sought (in	For In	Output power	Tx output power range of 25dB, in 0.1dB steps		
	brief)		For Input/ Output Data Interfaces ⇒ Regarding support for both IPv4 and IPv6, requested this to be changed to "IPv4 full functionality support"			
		For M ⇔	 Iodulator: Output power Tx output power range mentioned as "25dB,in 0.1dB steps" Should be mentioned as "- 25dB, in 0.1dB steps" which is the standard followed by most of the OEMs. 			
	ERNET India's response	Modif		tement is given below:		
	Modified Tender	a)	General Specificati	ons:		
	clause statement		Input /Output Data Interfaces			
				10/100Base-T Ethernet (optional)		
				IPv4 and IPv6 dual stack full functionality support		
				(Note:1. If IPv6 support & feature is not available in any of OEM's existing product which meets the		

38.	Tender clause no. & Page Tender clause statement	b) Modulator Output power Clause 3 of 5 (of Table f (SCPC VSAT links) Ma General features	-
		Optional	 The SCPC VSAT links Management system (NMS) shall support above features in MESH topology. The bidder shall provide the technical documentation in the bid. But it's price need not to be quoted. The system shall be expandable to support more than 30 SCPC VSAT links.
	Queries sought (in brief)	interface itself ⇒ Is this feature r	entioned are available only with Ethernet interface and Ethernet is optional as per 1 &2. required from Day1 in NMS?
		requirements, i	lelete Mesh optional feature. In the absence of exact mesh t is an open feature.
	ERNET India's response	At the time of I will be used / I	NMS purchase, optional feature of modem (i.e. Ethernet interface) purchased.
		Optional featur	e required from day-1. e is self explanatory.
39.	Tender clause no. &	➡ Thus, no chang Clause 3 of 5 (of Table 1	te in any clause/statement for NMS: Network Page 73
	Page	(SCPC VSAT links) Ma	

	T 1 1	O(1) m	
	Tender clause statement Queries sought (in brief) ERNET India's response Modified Tender clause statement	features on the The The The The The correst on the The equ Shat Regarding support f support IPv4 protocore Modified Tender class on the The on the The correst on the the The correst on the th	
40.	Tender clause no. &	Clause 4 of 5 (of Ta	ble for C-band BUC - Page 74
-0.	Page	5Watts or 10 Watts	
	Tender clause	Environmental	• Operating temperature : -20°C to + 60°C
	statement		 Relative Humidity : up to 100% Weather Protection and day IDC5
			 Weather Protection sealed to IP65 Operating Voltage : +15VDC to +60VDC
			 Operating Voltage : +15 VDC to +60 VDC Power Supply Interface : Common input via IFL
			 Size & weight: Small in size and low in weight
			 Easy to install at antenna.
			 It is a single integrated unit with built-in AC power supply.
			 All cables and connectors shall be included for its
			integration and installation to establish SCPC VSAT link
	Queries sought (in		to change as "Operating Voltage : +18VDC to +60VDC" since this is
	brief)		upon individual product design.
			to changed as "It is a single integrated unit with built-in AC or DC
	ERNET India's	power supp	use statement is given below:
	ERINET HIGHA S	woullieu Tender cla	iuse statement is given below.

response Environmental	 Operating temperature : -20°C to + 60°C Relative Humidity : up to 100% Weather Protection sealed to IP65 Operating Voltage : +15/18VDC to +60VDC Power Supply Interface : Common input via IFL Size & weight: Small in size and low in weight Easy to install at antenna. It is a single integrated unit with built-in AC or DC power supply. All cables and connectors shall be included for its integration and installation to establish SCPC VSAT link
------------------------	--

Annexure-II-D

41.	Tender clause no. & Page	Clause 6 (of Table for Do	own converter)	Page 79 & 80
	Tender clause statement	Frequency step size	1 kHz	
	Queries sought (in brief)	1KHz is not required for most applications. 125KHz step size is the standard for all communication requirements. 1KHz step will make the converter more expensive due to synthesiser cost. Requested to change to 125 KHz.		
	ERNET India's response	Modified Tender clause statement is given below:		
	Modified Tender clause statement	Frequency step size	125 kHz	
42.	Tender clause no. & Page	Clause 7 (of Table for Up	o converter)	Page 80
	Tender clause statement	Spurious		3m output (Non carrier related)
		-65 dBc @ 0 dE		m output (carrier related)
		Frequency Step Size	1KHz	
	Queries sought (in brief)	Spurious may be changed to -60 dBc @ 0 dBm output (carrier related) or better which is a reasonable specification for Up converter		
		⇒ 1KHz is not required for most applications. 125KHz step size is the standard for all communication requirements. 1KHz step will make the converter more expensive due to synthesiser cost. Requested to change to 125 KHz.		
	ERNET India's response	Modified Tender clause statement is given below:		
	Modified Tender clause statement	Spurious		Bm output (Non carrier related) m output (carrier related) or better
		Frequency Step Size	125 KHz	1

Annexure-III

43.	Tender clause no. &	Sr. 6 of Table	Page 81
	Page		
	Tender clause	Delivery of imported and indigenous remote	
	statement	Delhi to the user sites. (Any delay in arrangin	g the shipment related papers ie road permits,
		declarations, challans etc by ERNET India wi	ll not be accounted on Bidder's part).
	Queries sought (in	Do bidder need to deliver hardware 1st to ER	NET India warehouse in Delhi? Can we have
	brief)	keep the inventory in multiple warehouse in I	ndia based on ERNET's locations? Please
		specify.	
	ERNET India's	The bidder shall keep all inventories at his wa	rehouse in NCR (Delhi).
	response		

Ann	exure-IV	
44.	Tender clause no. &	Annexure-IV-A & B at page 91 &92
	Page	
	Queries sought (in	\Rightarrow We understand that all type of taxes and duties shall be considered in the Grand total
	brief)	for the declaration of L1 bid. Please confirm.
	ERNET India's	Yes, all types of taxes and duties shall be considered in the Grand total for the declaration
	response	of L1 bid.
45.	Tender clause no. &	Heading at Annexure-IV-B at page 92
	Page	
	Tender clause	ANNEXURE - IV B (For Local Equipment in Rupees)
	statement	
	Queries sought (in	Since items quoted in INR will not necessarily by Local Equipment, thus requested to
	brief)	change it to "Items quoted in INR"
	ERNET India's	The modified statement is as below:
	response	
	Modified Tender	ANNEXURE - IV B (For Items quoted in INR(Rupees))
	clause statement	

Annexure-VII

46.	Tender clause no. & Page	Sr 3.2 of Table	Page 99	
	Tender clause	"Number of support offices only w.r.t. VSAT business		
1	statement	(Please attach enclosure for furnishing full information)"		
	Queries sought (in	Requested to allow support offices, supporting the overall business of the bidder and not		
	brief)	only the VSAT business. Also , please allow third party manpower as field operations are		
		handled by third party manpower. However, the responsibility lies with the bidder.		
	ERNET India's	Please see Clause 3 of Section-E and 2nd para after clause 12 of Section-E which is self		
	response	explanatory in this regard. However, it is again clarified that the bidder may use third party manpower as field operations/support, but bidder shall be solely responsible for all the		
		deliverables from these subcontractors and under no circumstance shall transfer the		
		subcontractor's liabilities to ERNET India.		
47.	Tender clause no. & Page	Sr 6.1 of Table	Page 100	
	Tender clause	⇒ Column 'Turnover from VSAT related field'		
	statement	And		
		⇒ Column ' Total Turnover of the bidder'		
	Queries sought (in brief)	Requested to remove the Column 'Turnover from VSAT related field'		
	ERNET India's	Modified Tender clause statement is given below:		
	response			
	Modified Tender	⇒ Column 'Turnover from VSAT related field' has been removed.		
	clause statement	And		
		⇒ Column ' Total Turnover of the bidder' has been replaced with Total Turnover of		
		the bidder from Indian operations'		

Annexure-VIII

		Page 101
ge		
nder clause 1.0	Hub Uptime	
ement		
1.1	quarterly basis for 24x7x365 days of	Hub, Bangalore uptime of 99.9% averaged on peration meeting Network performance. The on the following formula:
1	der clause 1.0 ement	der clause 1.0 Hub Uptime ement 1.1 Bidder guarantees that ERNET VSAT H

Where, Hub port = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000- per day to ERNET India. Bidder shall ensure that all components installed at hub shall fonction in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, hut not later than 12 hours, in case of its non-replacement of the equipment within 12 hours, in case of its non-replacement of the equipment within 12 hours, the idder shall pay penalty of Rs. 10,000-' for that day. If bidder is unable to repair or replace the failury equipment at Hub within 24 hours, the bidder shall pay penalty of Rs. 30,000-' per day per equipment to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. .3 Penaltics whichever shall be at the higher side shall be imposed. .4 Hub means all items at Hub including SCPC items/modems. .9 Requested to onderate this clause from 10 days to 45 days for invoking BG. ENNET India's "symmetry" Modified Tender clause statement is given below: "symmetry" Notified Tender clause statement is given below: "symmetry" Hub typtime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24X7x365 days operation meeting Network performance. The Hub bug meeting VAx 50, 5000-', per day to ERNET India. Bidder shall as preating of Rs. 5,0000- per day to ERNET India. Bidder shall apy penalty		Hub Uptime (HU) in % = $((Hub_{POT} - Hub_{DT}) / Hub_{POT})^*100$
Hub ror = Hub power on time Hub rr = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (thirdware/software) at hub, it shall be repaired / replaced immediately, but not later than 12 hours, the bidder shall pay penalty of Rs. 10,000-f or that day. If bidder is unable to repair or replace the faulty equipment at Hub within 24 hours, the bidder shall pay penalty of Rs. 30,000- per day per equipment to ERNET India subsequently. 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Charantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 1.3 Penalties whichever shall be at the higher side shall be imposed. 1.4 Hub means all tiems at Hub including SCPC items/modems. Queries sought (in brief) Requested to change this clause and link to uprime SLA commitment & also allow replacement/repair can be done within 2 weeks of time. exponse Modified Tender clause statement is given below: clause statement 1.0 Hub Uptime 1.1 Bidder shall pay penalty of Rs. 50000- per day to ERNET India. Hub rory = Hub power on time Hub Uprime (HU) in % = ((Hub ror) - Hub ror)/ Hub ror)*100		Where
Hub pr = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000 ² , per duy to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment time that/ware/software) at hub, it shall be repaired / replaced immediately, but not later than 12 hours. In case of its non-replacement of the equipment with II 2 hours, the bidder shall pay penalty of Rs. 10,000 ² , for that day. If bidder is unable to repair or replace the faulty equipment at Hub bis not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. Queries sought (in bit of the means all items at Hub including SCPC items/moders. Queries sought (in bit of the means all items at Hub including SCPC items/moders. • Requested to change this clause and link to uptime SLA commitment & also allow replacement/epair can be done within 2 weeks of time. • Requested to moderate this clause from 10 days to 45 days for invoking BG. ERNET India's requested to moderate this clause from 10 days to 45 days for invoking BG. In Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime (HU) in % = ((Hub pror - Hub pror) / Hub pror)*100 Where, Hub pror = Hub dower on time Hub by r = Hub dower on time thub by r = Hub dower on time Hub by r = Hub dower on tine. Hub Uptime (HU) in % = (Gl		
Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 12 hours. In case of its non-replacement of the equipment to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. Queries sought (in) * * Requested to change this clause and link to uptime SLA commitment & also allow "eplacement/repair can be done within 2 weeks of time. * Requested to change this clause and link to uptime SLA commitment & also allow "eplacement/repair can be done within 2 weeks of time. * Requested to change the this clause from 10 days to 45 days for invoking BG. ERNET India's response Modified Tender clause statement is given below: response 1.0 Hub Uptime 1.1 Bidder shall pay penalty of Rs. 50,0000/- per day to ERNET India. Hub Uptime (HU) in % = ((Hub _{FOT} – Hub _{DT}) / Hub _{FOT} *100 Where, Hub Uptime (HU) in % = ((Hub _{FOT} – Hub _{DT}) / Hub _{FOT} *100 Where, Hub by mar Hub down time In case required Hub uptime fails below 99.5% (averaged on q		
condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired /replaced immediately, but not later than 12 hours. Ine see of its non-replacement of the equipment within 12 hours, the bidder shall pay penalty of Rs. 10,000- per day per equipment to ERNET India subsequently. 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 1.3 Penalties whichever shall be at the higher side shall be imposed. 1.4 Hub means all items at Hub including SCPC times/modents. Pueries sought (in bifs) PRequested to change this clause and link to uptime SLA committent & also allow replacement/repair can be done within 2 weeks of time. PRENET India's Modified Tender clause statement is given below: response Modified Tender clause statement is given below: response I.0 Hub Uptime 1.1 Bidder shall pay penalty of Rs. 50,0000- per day to ERNET india. Bidder shall pay penalty of Rs. 50,000- per day to ERNET india. Bidder shall pay penalty of Rs. 50,000- per day to ERNET india. In thub Uptime (HU) in % = ((Hub _{POT} – Hub _{DT}) / Hub _{POT})*100 Where, Hub Uptime (HU) in % = fails below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000- per day t		
1.3 Penaltics whichever shall be at the higher side shall be imposed. Hub means all items at Hub including SCPC items/modems. Queries sought (in brief) Pequested to change this clause and link to uptime SLA commitment & also allow replacement/repair can be done within 2 weeks of time. Pequested to moderate this clause from 10 days to 45 days for invoking BG. ERNET India's response Modified Tender clause statement is given below: Modified Tender clause statement 1.0 Hub Uptime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub ror = Hub power on time Hub Uptime (HU) in % = ((Hub POT – Hub DT) / Hub POT)*100 Where, Hub POT = Hub power on time Hub DT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipm		 condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 12 hours. In case of its non-replacement of the equipment within 12 hours, the bidder shall pay penalty of Rs. 10,000/- for that day. If bidder is unable to repair or replace the faulty equipment at Hub within 24 hours, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India subsequently. 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall
1.4 Hub means all items at Hub including SCPC items/modems. Queries sought (in brief) ⇒ Requested to change this clause and link to uptime SLA commitment & also allow replacement/repair can be done within 2 weeks of time. ERNET India's response Modified Tender clause statement is given below: Modified Tender clause statement 1.0 Hub Uptime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub port = Hub power on time Hub Dptime (HU) in % = ((Hub port - Hub DT) / Hub port)*100 Where, Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 5,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 5,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 3,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s).<		1
brief) ⇒ Requested to moderate this clause from 10 days to 45 days for invoking BG. ERNET India's Modified Tender clause statement is given below: response 1.0 Hub Uptime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub Uptime (HU) in % = ((Hub _{POT} – Hub _{DT}) / Hub _{POT})*100 Where, Hub por = Hub power on time Hub _{DT} = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment to Lart than 48 hours. If bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India subsequently. But, in case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.		1.4 Hub means all items at Hub including SCPC items/modems.
 ⇒ Requested to moderate this clause from 10 days to 45 days for invoking BG. ERNET India's response Modified Tender clause statement is given below: Tesponse Modified Tender clause statement I.0 Hub Uptime I.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub Uptime (HU) in % = ((Hub _{POT} – Hub _{DT}) / Hub _{POT})*100 Where, Hub _{POT} = Hub power on time Hub _{DT} = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replace the faulty equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India subsequently. In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		
response Journal of the statement Modified Tender clause statement 1.0 Hub Uptime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub Uptime Hub Uptime (HU) in % = ((Hub POT – Hub DT) / Hub POT)*100 Where, Hub POT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours, the bidder is unable to repair or replace the faulty equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India ather 24 hours of the occurrence of the fault in the item(s). 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.	bilei)	
Modified Tender clause statement 1.0 Hub Uptime 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub Uptime (HU) in % = ((Hub POT – Hub DT) / Hub POT)*100 Where, Hub poT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.		Modified Tender clause statement is given below:
clause statement 1.1 Bidder guarantees that ERNET VSAT Hub, Bangalore uptime of 99.9% averaged on quarterly basis for 24x7x365 days operation meeting Network performance. The Hub Uptime will be calculated based on the following formula: Hub Uptime (HU) in % = ((Hub POT – Hub DT) / Hub POT)*100 Where, Hub por = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or relace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.		1 0 Hub Untime
 Where, Hub POT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 	clause statement	quarterly basis for 24x7x365 days operation meeting Network performance. The
 Hub POT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		Use Uniting (IIII) in θ = ((II) b = Use) / Use)*100
 Hub _{DT} = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		
 Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		
 condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India subsequently. 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		Where, Hub _{POT} = Hub power on time
 faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). 1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid. 		Where, Hub $_{POT}$ = Hub power on time Hub $_{DT}$ = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the
1.2 In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.		 Where, Hub POT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall
		 Where, Hub _{POT} = Hub power on time Hub _{DT} = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder is unable to repair or replace the faulty equipment at Hub within 48 hours, the bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the
1.3Penalties whichever shall be at the higher side shall be imposed.1.4Hub means all items at Hub including SCPC items/modems.		 Where, Hub POT = Hub power on time Hub DT = Hub down time In case required Hub uptime falls below 99.5% (averaged on quarterly basis), the Bidder shall pay penalty of Rs. 50,000/- per day to ERNET India. Bidder shall ensure that all components installed at hub shall function in good condition. In case of failure of any equipment (hardware/software) at hub, it shall be repaired / replaced immediately, but not later than 48 hours. If bidder shall pay penalty of Rs. 5,000/- per day per equipment to ERNET India subsequently. But, in case Hub become non-functional due to non-repair or non-replacement of faulty item at Hub, the bidder shall pay penalty of Rs. 30,000/- per day per equipment to ERNET India after 24 hours of the occurrence of the fault in the item(s). In any case if the Hub is not made operational for 10 days from the time of reporting of fault, the Bank Guarantees provided by the Bidder to ERNET India shall be invoked and any payment dues and AMC pertaining to this network shall not be paid.
